

Dynabox 350 12V DC

Cold-water high-pressure cleaners, 350 bar(5.075 PSI)

Highlights

The powerful Dynabox 350 12 V hot-water unit, offering a working pressure of up to 350 bar (5,075 PSI), is the ideal complement for all DYNAJET Trolleys. Simply connect on the high-pressure side between the high-pressure cleaner and the cleaning tool and, with high-pressure hot water of up to 95 °C, you will already be achieving results which are not possible with conventional cold-water systems. The other special features of the Dynabox 350 12 V are, of course, its light weight, small dimensions and its easy-loading and easy-transportation characteristics. What is more, the Dynabox 350 12 V works with a 12 V supply voltage. This means that no 230 V power cable is necessary, because the Dynabox 350 12 V can be easily connected to and operated via the combustion-driven DYNAJET Trolleys which are equipped with sockets as standard.



Standard equipment:

- Mechanical safety valve to act as a safeguard
- Manual thermostat for temperature regulation and as an on/off switch
- Safety pressure switch



DYNAJET 350 MG

TECHNICAL DATA

System	Hot-water generators
Type	Trolley/Box
Pressure class	350 bar (5.075 PSI)

Pressure

Pressure class	350 bar (5.075 PSI)
Pressure variable	No
Minimal pressure	40 bar (580 PSI)

Hydraulics

Minimum flow rate	7 l/min (1.85 USgal/min)
Maximum flow rate	21 l/min (5.56 USgal/min)

Threaded connection

Input port	M22x1,5 (ET)
Output port	M22x1.5 ET

Drive

Voltage and frequency	12 V direct current
Volume fuel tank	Approx. 18 l (4.76 USgal)

Others

Chassic	4 wheels
Weight in kg	130.0
Dimensions (L/W/H)	80 x 75 x 90 cm
Heating power oil burner/Dynabox	Max. 67 kW (94 Hp)
Temperature increase (Dynabox system only)	Ca. 55 °C at 21 l/min
Article number	1492060

Standard equipment

Standard equipment operating manual, Diesel burner for hot water, mechanical safety valve to act as a safeguard, manual thermostat for temperature regulation and as an on/off switch, safety pressure switch, outlet hose connection, flow controller for water flow monitoring, flame monitoring via photo cells in the combustion chamber, inspection glass for visual inspections

DYNAJET 350 mg

DYNAJET provides a long vairyety of accessories for:

- Cleaning squares, stations & car parks
- Removal of concrete for renovation
- Weed control
- Cleaning & paint stripping ships
- Industrial cleaning
- Removing chewing gum
- Removal of graffiti
- Cleaning formwork
- Cleaning scaffolding
- Cleaning construction machinery
- Cleaning roofs
- Facade renovation
- Rust stripping of metal parts
- Tank & container cleaning
- Debarking trees
- Cleaning monuments
- Eco-Friendly Cleaning for Solar
- Installations
- Agricultural Cleaning



Kit: Water-sandblasting WSS
500 Index 00.0550 – 350me,
350mg



Protective suit



Floor cleaning system DFS 350
VAC 350 bar



Roof cleaning system
DRS 500 bar

Dealer:



Double spray lance
M22x1,5A – 500bar



Rotating nozzle shape F
050 Index 20.0550-20°